

An Atlas-Assisted Method for Limited-Angle Cone-Beam Tomography

**Sadowsky, Ofri^{*}, Ramamurthi, Krishnakumar, Taylor, Russell H., Prince, Jerry, L.
Johns Hopkins University, Baltimore, MD, USA**

This poster presents an atlas-assisted method for artifact reduction in CT-like tomographic reconstruction of anatomy from an incomplete set of cone-beam X-ray projections obtained from a C-arm.

A complete cone-beam reconstruction using standard techniques (e.g., Feldkamp) requires a sweep of (at least) 180 degrees + cone-angle. However, the angle through which a C-arm may sweep is often limited due to patient/O.R. setup. Reconstructed images from such incomplete sweeps suffer from strong limited-angle artifacts because of missing information. Our work is aimed at reducing these artifacts by using statistical knowledge of the patient anatomy to compensate for the missing data.

We present a 3-D reconstruction method that uses an anatomical atlas of a bone as the source of statistical knowledge. Our atlas is constructed from a collection of patient CT scans, and includes the average shape and density of the bone, and statistical variations of both. To perform the reconstruction, we first select a small set of projections from the set of patient cone-beam images, and use them as registration targets in a deformable 2-D/3-D registration. The registration algorithm consists of three steps: rigid transformation, deformation based on the atlas statistics, and local template-matching deformation, while maximizing mutual information. With the registered model, we compute simulated projections of the atlas from those view angles that were missing from the original cone-beam scan. Representation of the atlas as barycentric density polynomials over tetrahedral mesh elements provides a closed formula for generating the simulated projections. We complete the original set of patient images with the set of atlas-based simulated projections and perform a traditional cone-beam reconstruction algorithm on this set to obtain our final 3-D reconstruction.

We have tested our method using a statistical atlas of a hemipelvis and digitally reconstructed radiographs (DRRs) generated from a patient's CT scan for the purpose of patient data. Our initial qualitative assessment shows a significant reduction of artifacts when the atlas is used to complete missing data. Our method combines modeling of biological knowledge-base, in the form of the statistical atlas, and an innovative computational approach in 3-D reconstruction. Improving the accuracy of limited angle-range cone-beam reconstruction can significantly improve patient treatment in emergency or field units.

The project is supported in part by the National Science Foundation and by Johns Hopkins University internal funds, through the CISST-ERC.